



Full range of subcontracting

Hot Strip, Cold Strip, Stainless Steel, Sheet Metal, Non-ferrous Metal

SLITTING AND TRIMMING

	SLITTING LINE 1	SLITTING LINE 2
Strip thickness [mm]	2 – 12	1 – 5 (< 1 upon request)
Operating weight [t]	max. 32	max. 13,5
Coil width [mm]	max. 1.760	max. 950
Strip size [mm]	min. 24, max. spreading 1740	min. 18, max. spreading 950
ROD max. [mm]	uncoiling 2100, coiling 2040	uncoiling 2055, coiling 2020
RID [mm]	uncoiling 508/610/765, coiling 508/610	uncoiling Konus, coiling 508

COLD ROLLING

Strip thickness [mm]	1 – 10
Operating weight [t]	max. 4,5
Strip size [mm]	max. 320
ROD [mm]	max. 2000
RID [mm]	uncoiling 400/508/610, coiling 508

STRIP EDGE TRIMMING (THREADING, REALIGNING)

Strip thickness [mm]	1 – 10
Operating weight [t]	max. 4,5
Strip size [mm]	Realigning max. 320, Threading max. 370
ROD [mm]	max. 2000
RID [mm]	uncoiling 400/508/610, coiling 508

CONTACT

Main	Phone +49 2331 / 18733 - 0	info@erbe-flachstahl.de
Stefan Dorn (Plant Management)	Phone +49 2331 / 18733 - 12	
Patrick Nolte (Vice Sales Management)	Phone +49 2331 / 18733 - 14	